FAA-E-2373
AMENDMENT-1
3 June 1969

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION SPECIFICATION

ADHESIVE COMPOUND, TWO-COMPONENT
FOR
SEALING WIRE IN FLEXIBLE PAVEMENT

This amendment forms a part of FAA-E-2373 dated 26 December 1968.

Page 1, paragraph 1.1: Delete "selected bitumen" and insert "bitumen-hardener mixture."

Page 2, paragraph 2.1.2: Delete "Fed-Std-141 Paint, Varnish, Lacquer, and Related Materials; Methods of Inspection, Sampling and Testing". Delete "Fed-Std-158 Cements, Hydraulic, Sampling, Inspection and Testing". Delete "Fed-Std-406" and insert "Fed Test Method Std. No. 406".

Page 3, paragraph 3.2.2: Delete "modified so" in line 2 and insert "modified with an aliphatic polyamine so".

Page 3, paragraph 3.3.1, Table I: Delete "Viscosity, poises at 25°C (77°F)". Delete "1.03" and insert "1.08".

Page 4, paragraph 3.3.3, Table III: Delete "Fed Test Method 1011" and insert "Fed Test Method Std. No. 406, Method 1011". Delete "Fed Test Method 6081" and insert "Fed Test Method Std. No. 406, Method 6081". Delete "Fed Test Method 7011" and insert "Fed Test Method Std. No. 406, Method 7011". Delete "Fed Test Method 7031" and insert "Fed Test Method Std. No. 406, Method 7031".

* * * * *